



BrilliantTouch® Physical Characteristics & Care of Product Information

BrilliantTouch® accessibility signage is produced using a revolutionary polycarbonate first surface combined with a unique multi-layer system. The result is a versatile sealed unit product for all user applications. BrilliantTouch® is distributed globally and conforms to the accessibility standards of the United Kingdom, the United States, Australia and Canada.

- BrilliantTouch® exceeds the requirements of the Disability Discrimination Act of 1995 for Grade 1 Braille and tactile signage, including the specifications for proper kerning, precise height requirements of both Braille and tactile elements, matte surface for glare reduction, appropriate colour contrasts, font selections and more.
- All graphics and text are sub-surface. Cannot be picked off, scratched or tampered with.
- Suitable for high-traffic areas. BrilliantTouch® signs are vandal-resistant and can be cleaned easily with strong disinfectants and cleaners without damage to sign surface. Even sprayed on graffiti can be removed with ease with citrus-based cleaners or petroleum-based solvents.
- Raised pictograms and letters have soft-shouldered edges and will not hurt fingertips. Dirt and bacteria, which may accumulate around raised features, can be easily and hygenically wiped off.
- Fire retarding: Surface-burning characteristics USA National Fire Protection Association 255.
- Flame spread index: 15
- Smoke developed index: 110. Level 1, Class A rating. Self-extinguishing.
- Pencil hardness: H (ASTM D3363-92)
- Shear strength: High
- Graphics and text resist fading. No first-surface paint to chip or peel.
- Interior and exterior grades.

For information contact:

Eye Catch Signs Ltd. International
001-902-423-3309
www.eyecatchsigns.com
sales@eyecatchsigns.com